

**EUROPEAN OAK
5G FLOORING
WIDE PLANK
1820/190/13.5 MM**



PRONTO
READY TO GO

ENGINEERED OAK FLOORING



TECHNICAL SPECIFICATIONS

» Key Features

Engineered to exacting standards. Manufactured from environmentally certified resource. Extremely stable with excellent wear resistance. Wear layer can be refurbished and rejuvenated when required.

» Description

Engineered European Oak Flooring, Valinge Patented 5g Click.

» Size & Length

190mm width, 1820mm length, 13.5mm thickness.
2.5mm Solid Oak wear layer.

» Valinge 5g Click

Quick and easy to lay - no dust, no smell and no mess.
Please consult with your supplier for specific site install guidelines prior to installation.

» Grade & Surface

A/B/C/D Rustic Grade contains knots and split defects that are filled and patched to compliment surface colour and character. Allows for other rustic features such as sapwood, raised grain, along with colour variation to enhance rustic character. Visual appearance will suit those seeking a heavily featured rustic grade for their installations. Pre-finished, European PU matte coating. Light wire brush surface.

» Profile

Valinge 5g Click. Micro Bevelled Edges.

» VOC Emissions

<E1, (Below World Health Organisation Levels)

Chicory



Ponderosa



Portofino



Regal Oak



Santorini



Spindrift



RESELLER ENQUIRIES

South Australia

ABN 63 600 454 215
27 Pambula Street,
Regency Park SA 5010
t +61 8 8268 8010
f +61 8 268 8919
sa@preferencefloors.com.au

Queensland

ABN 81 169 158 990
6/ 268 Evans Road,
Salisbury QLD 4107
t +61 7 3875 1688
f +61 7 3875 1788
qld@preferencefloors.com.au

Victoria

ABN 34 151 422 927
19 Lanyon Street,
Dandenong South VIC 3175
t +61 3 9794 5111
f +61 3 9794 5133
vic@preferencefloors.com.au

New South Wales

ABN 40 117 801 037
Unit A/31 Sturt Street,
Smithfield NSW 2164
t +61 2 9738 1189
f +61 2 9738 1199
sales@preferencefloors.com.au

For specification or reseller support contact:

www.preferencefloors.com.au