



*Prefinished Engineered Oak flooring,
beautiful, natural & timeless.*

Woodland Euro Oak

Quality Is Our Attitude



Proud to be a Member of the
atfa
Australian Timber Flooring Association



TOPDECK FLOORING



Technical Specifications

Type

Engineered Oak Flooring, 4mm Timber Veneer on 11 mm Plywood

Manufacturing Process

Brushed, white washed, smoked or stained

Locking System

Tongue & Groove (T&G)

Dimensions

1900mm x 190mm x 15mm

Structural Warranty

25 years residential 10 years commercial

Coating Warranty

10 years residential 5 years commercial

Coating Finish

9 layers of Treffert matt lacquered finish

Hardness

Janka 6.8kn

Colour Collection

Cottage, Grigio, Limed Wash, Marrone, Latte, Smokey Grey, Vino-Blanco

Slip Rating

D1 Pass achieved as per Slip Resistance AS 4586 (2013)

Fire Rating

CHF (Critical Heat Flux / Critical Radiant Flux) 6.9kW/m²

Environmental & Quality Certificates

VOC E0 (0.014Mg/m³)

ISO9000 Quality control System and ISO14000 Environment Control System, CE and FSC certificate



Combining Quality & Environmental control standards throughout the manufacturing process.



ENGINEERED Prefinished European Oak
15mm thickness consisting of a 4mm Oak wear layer bonded to a superior 11mm eucalyptus / birch blend plywood.

As timber is a natural product, the colour, grain and feature patterns will vary in the flooring as in the printed media.

www.topdeckflooring.com.au
16 Salisbury St, Silverwater, NSW 2128 | Ph: 9748 2288 | Fax: 9748 2266

Woodland Euro Oak Milano Collection



Cottage Oak



Grigio



Limed Wash



Marrone Oak



Oak Latte



Smokey Grey



Vino-Blanco