

20
year
FINISH
WARRANTY

LIMITED
lifetime
STRUCTURAL
WARRANTY



Fiddleback
Australian Hardwood



Blackbutt

Your Peace of Mind

Introducing our unique Fiddleback Engineered Australian Hardwood collection.

It's available in the ever popular Spotted Gum and Blackbutt. Fiddleback wear layers combine the classic features of our Australian Eucalyptus bonded onto an ever reliable Plywood core. This creates an authentic Australia timber visual with the associated stability and durability of an engineered timber construction.



Key Features

- > Extremely stable with excellent wear resistance
- > Spotted Gum Janka 11kN
- > Impact resistant, durable and stable
- > Blackbutt Janka 9.1 kN
- > Available in the resource efficient 0.6 mm Micro-veneer or the traditional 3.0 mm sawn cut wear layer. Both thicknesses provide excellent durability for residential use.

Variety of Finishes

Surface finishes include smooth or light wire brushed textures, pre-finished with European water based multi-coat PU lacquer. All sizes display Micro-bevel 4 sides to enhance the natural plank visual.

The Fiddleback range is ideal for interior decors with a Click floating installation for fast and easy install.

Description	Surface	Size	Sqm/Ctn	Ctns/Pallet	M-Bevel
Blackbutt Semi-Gloss - 0.6mm	Smooth	1860x136x12/0.6mm	1.771	77	Yes 4 Sides
Blackbutt Matte - 0.6mm	Brushed	1860x136x12/0.6mm	1.771	77	Yes 4 Sides
Spotted Gum Semi-Gloss - 0.6mm	Smooth	1860x136x12/0.6mm	1.771	77	Yes 4 Sides
Spotted Gum Matte - 0.6mm	Brushed	1860x136x12/0.6mm	1.771	77	Yes 4 Sides
Blackbutt Matte - 3mm	Smooth	1860x189x14/3.0mm	2.109	55	Yes 4 Sides
Spotted Gum Matte - 3mm	Smooth	1860x189x14/3.0mm	2.109	55	Yes 4 Sides

Spotted Gum

Blackbutt



Smooth Semi-Gloss, 0.6mm
1860x136x12/0.6mm



Brushed Matte, 0.6mm
1860x136x12/0.6mm



Smooth 10% Matte, 3mm
1860x189x14/3.0mm

Spotted Gum



Smooth Semi-Gloss, 0.6mm
1860x136x12/0.6mm



Brushed Matte, 0.6mm
1860x136x12/0.6mm



Smooth 10% Matte, 3mm
1860x189x14/3.0mm



Spotted Gum

Technical Specifications

» Grade & Surface

Standard & Better.

Will display natural characteristics such as knots, filled voids and gum vein. Slight checking in wear layer is acceptable.

» Sizes

136 x 12/0.6 x 1860 mm: Pcs/Ctn: 7 pcs, Sqm/Box: 1.771.

Ctns/Pallet: 77. Sqm/Pallet: 136.367m², Weight/Pallet: 1250 Kg.

189 x 14/3.0 x 1860 mm: Pcs/Ctn: 6 pcs, Sqm/Box: 2.109.

Ctns/Pallet: 55. Sqm/Pallet: 115.995 m², Weight/Pallet: 1350 Kg.

» Profile

Patented Click format, floating or direct fix installation.

Micro Bevelled edges, 4 sides.

» Structure

Genuine Australian Eucalyptus wear layers over a stable Plywood base.

» Cartons

Contain nested combination shorts.

» Coating

PU Semi-gloss, approx. 40% gloss level is smooth face.

PU Matte, approx. 10% gloss level in both brushed and smooth face.

Reseller Enquiries

Adelaide

t +61 8 8268 8010
sa@preferencefloors.com.au

Brisbane

t +61 7 3875 1688
qld@preferencefloors.com.au

Melbourne

t +61 3 9794 5111
vic@preferencefloors.com.au

Sydney

t +61 2 9738 1188
sales@preferencefloors.com.au